# APEXIOR COMPOUND NO.3





Metal Tek® Apexior Compound No. 3 is specially formulated as an anti-corrosive coating for metal surfaces such as storage tanks that is in contact with fresh or salt water. It is suitable for wet surfaces of a temperature below 50°C or dry and hot surfaces of a temperature up to 200°C.

#### **FEATURES**

Air dries, easy to apply
Easily re-coatable
Suitable for surface in contact with fresh and salt water
Excellent anti-corrosive performance
Prevents scale buildip
Surface tolerant features.

#### **APPLICATION**

Typical applications for condensers, cold water tanks, centrifugal pumps, piping, ducting, air coolers and metal boilers.

## **INSTRUCTION**

Remove all surface imperfections that will induce premature coating system failure. Chip or scrape off weld splatter. Grind down sharp and rough edges, gauges and pits. Redisperse any settled-out pigments by stirring with a paint paddle followed by thorough mixing to a uniform consistency with an explosion-proof or air driven power mixer. Do not open containers until ready to use. May be applied by conventional spray, airless spray or brush. Do not apply in heavier films than specified since blistering may occur. During application, ventilate area with high volume of air.

### SAFETY HANDLING CONSIDERATION

Keep away from direct sun light or from heat and flame. Do not breathe vapors. Ensure to use in a well-ventilated area during mixing and application. Wear an appropriate protective gloves and safety goggles while handling the product.

Avoid eye and skin contact. In case of of contact with skin or eyes, wash and rinse with water immediately. Get medical attention if irritation develops and persists.

Store in a cool and dry place.

More details, please refer to the MSDS.

## **SPECIFICATIONS**

Physical state	Liquid paste
Odour	Mild
рН	Not applicable
Solubility in water	Slight
Specific gravity	1.10
Vapor pressure	Less than 5mmHg at 27°C
Vapor density	Not applicable
Evaporation rate	Not applicable
Color	Grayish black
Content	3 kg
IMPA Code	450562

Disclaimer: Accuracy of all technical data and information are provided to the best knowledge of the manufacturer. Properties, specifications and application parameters are subject to change without notice. The manufacturer does not undertake any liability of any kind whatsoever.