



## Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 17

LOCTITE EA 9480 DC50ML EN/DE

SDS No. : 338557  
V003.0

Revision: 03.07.2020

printing date: 04.07.2020

Replaces version from: 01.06.2020

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

LOCTITE EA 9480 DC50ML EN/DE

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Epoxy resin

#### 1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Adhesives

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

Fax-no.: +44 (1442) 278071

ua-productsafety.uk@henkel.com

#### 1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (CLP):

Skin irritation

Category 2

H315 Causes skin irritation.

Serious eye irritation

Category 2

H319 Causes serious eye irritation.

Skin sensitizer

Category 1

H317 May cause an allergic skin reaction.

Chronic hazards to the aquatic environment

Category 2

H411 Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

##### Label elements (CLP):

Hazard pictogram:



Contains

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight  $\leq 700$ )

## 1,4-bis(2,3 epoxypropoxy)butane

<b>Signal word:</b>	<b>Warning</b>
<b>Hazard statement:</b>	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H411 Toxic to aquatic life with long lasting effects.
<b>Supplemental information</b>	EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
<b>Precautionary statement:</b> <b>Prevention</b>	P273 Avoid release to the environment. P280 Wear protective gloves.
<b>Precautionary statement:</b> <b>Response</b>	P302+P352 IF ON SKIN: Wash with plenty of soap and water. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

**2.3. Other hazards**

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****General chemical description:**

Epoxy resin

**Declaration of the ingredients according to CLP (EC) No 1272/2008:**

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	01-2119456619-26	50- 100 %	Skin Irrit. 2 H315 Skin Sens. 1 H317 Eye Irrit. 2 H319 Aquatic Chronic 2 H411
1,4-bis(2,3 epoxypropoxy)butane 2425-79-8	219-371-7 01-2119494060-45	1- < 5 %	Acute Tox. 4; Oral H302 Acute Tox. 4; Dermal H312 Acute Tox. 4; Inhalation H332 Skin Irrit. 2 H315 Skin Sens. 1 H317 Eye Irrit. 2 H319 Aquatic Chronic 3 H412
Quartz (SiO <sub>2</sub> ), <1% respirable 14808-60-7	238-878-4	1- < 5 %	
Titanium dioxide 13463-67-7	236-675-5 01-2119489379-17	1- < 5 %	

For full text of the H - statements and other abbreviations see section 16 "Other information".

Substances without classification may have community workplace exposure limits available.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

#### Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

#### Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

#### Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

SKIN: Redness, inflammation.

SKIN: Rash, Urticaria.

EYE: Irritation, conjunctivitis.

### 4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media:

Carbon dioxide, foam, powder

#### Extinguishing media which must not be used for safety reasons:

None known

### 5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and nitrogen oxides (NO<sub>x</sub>) can be released.

### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

#### Additional information:

In case of fire, keep containers cool with water spray.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

### 6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

### 6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Wash spillage site thoroughly with soap and water or detergent solution.

Dispose of contaminated material as waste according to Section 13.

### 6.4. Reference to other sections

See advice in section 8

---

**SECTION 7: Handling and storage**

---

**7.1. Precautions for safe handling**

Use only in well-ventilated areas.

Avoid skin and eye contact.

Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.

See advice in section 8

**Hygiene measures:**

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

**7.2. Conditions for safe storage, including any incompatibilities**

Store in a cool, well-ventilated place.

Refer to Technical Data Sheet

**7.3. Specific end use(s)**

Epoxy resin

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational Exposure Limits

Valid for  
Great Britain

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Kaolin 1332-58-7 [KAOLIN, RESPIRABLE DUST]		2	Time Weighted Average (TWA):		EH40 WEL
Mica 12001-26-2 [MICA, RESPIRABLE]		0,8	Time Weighted Average (TWA):		EH40 WEL
Mica 12001-26-2 [MICA, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		EH40 WEL
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		EH40 WEL
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE, RESPIRABLE]		4	Time Weighted Average (TWA):		EH40 WEL
Quartz (SiO <sub>2</sub> ) 14808-60-7 [SILICA, RESPIRABLE CRYSTALLINE]		0,1	Time Weighted Average (TWA):		EH40 WEL
Quartz (SiO <sub>2</sub> ) 14808-60-7 [RESPIRABLE CRYSTALLINE SILICA DUST]		0,1	Time Weighted Average (TWA):		EU OELIII

#### Occupational Exposure Limits

Valid for  
Ireland

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Kaolin 1332-58-7 [KAOLIN, RESPIRABLE DUST]		2	Time Weighted Average (TWA):		IR_OEL
Mica 12001-26-2 [MICA (RESPIRABLE FRACTION)]		3	Time Weighted Average (TWA):		IR_OEL
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		IR_OEL
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE, TOTAL INHALABLE DUST]		10	Time Weighted Average (TWA):		IR_OEL
Quartz (SiO <sub>2</sub> ) 14808-60-7 [QUARTZ, RESPIRABLE DUST (SEE CRYSTALLINE SILICA)]		0,1	Time Weighted Average (TWA):		IR_OEL
Quartz (SiO <sub>2</sub> ) 14808-60-7 [RESPIRABLE CRYSTALLINE SILICA DUST]		0,1	Time Weighted Average (TWA):		EU OELIII

**Predicted No-Effect Concentration (PNEC):**

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	aqua (freshwater)		0,006 mg/l				
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	aqua (marine water)		0,001 mg/l				
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	sewage treatment plant (STP)		10 mg/l				
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	sediment (freshwater)				0,341 mg/kg		
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	sediment (marine water)				0,034 mg/kg		
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	Soil				0,065 mg/kg		
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	oral				11 mg/kg		
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	aqua (intermittent releases)		0,018 mg/l				
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	marine water - intermittent		0,002 mg/l				
1,4-Bis(2,3-epoxypropoxy)butane 2425-79-8	aqua (freshwater)		0,024 mg/l				
1,4-Bis(2,3-epoxypropoxy)butane 2425-79-8	oral				0,028 mg/kg		
1,4-Bis(2,3-epoxypropoxy)butane 2425-79-8	sediment (freshwater)				0,084 mg/kg		
1,4-Bis(2,3-epoxypropoxy)butane 2425-79-8	Soil				0,003 mg/kg		
1,4-Bis(2,3-epoxypropoxy)butane 2425-79-8	aqua (marine water)		0,002 mg/l				
1,4-Bis(2,3-epoxypropoxy)butane 2425-79-8	sewage treatment plant (STP)		100 mg/l				
1,4-Bis(2,3-epoxypropoxy)butane 2425-79-8	sediment (marine water)				0,008 mg/kg		
Titanium dioxide 13463-67-7	aqua (freshwater)						no hazard identified
Titanium dioxide 13463-67-7	aqua (marine water)						no hazard identified
Titanium dioxide 13463-67-7	sewage treatment plant (STP)						no hazard identified
Titanium dioxide 13463-67-7	sediment (freshwater)						no hazard identified
Titanium dioxide 13463-67-7	sediment (marine water)						no hazard identified
Titanium dioxide 13463-67-7	Soil						no hazard identified
Titanium dioxide 13463-67-7	Aquatic (intermit. releases)						no hazard identified
Titanium dioxide 13463-67-7	Predator						no hazard identified

**Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
reaction product: bisphenol-A-(epichlorhydrin) 25068-38-6	Workers	dermal	Acute/short term exposure - systemic effects		8,33 mg/kg	
reaction product: bisphenol-A-(epichlorhydrin) 25068-38-6	Workers	Inhalation	Acute/short term exposure - systemic effects		12,25 mg/m3	
reaction product: bisphenol-A-(epichlorhydrin) 25068-38-6	Workers	dermal	Long term exposure - systemic effects		8,33 mg/kg	
reaction product: bisphenol-A-(epichlorhydrin) 25068-38-6	Workers	Inhalation	Long term exposure - systemic effects		12,25 mg/m3	
reaction product: bisphenol-A-(epichlorhydrin) 25068-38-6	General population	dermal	Acute/short term exposure - systemic effects		3,571 mg/kg	
reaction product: bisphenol-A-(epichlorhydrin) 25068-38-6	General population	dermal	Long term exposure - systemic effects		3,571 mg/kg	
reaction product: bisphenol-A-(epichlorhydrin) 25068-38-6	General population	oral	Acute/short term exposure - systemic effects		0,75 mg/kg	
reaction product: bisphenol-A-(epichlorhydrin) 25068-38-6	General population	oral	Long term exposure - systemic effects		0,75 mg/kg	
reaction product: bisphenol-A-(epichlorhydrin) 25068-38-6	General population	inhalation	Acute/short term exposure - systemic effects		0,75 mg/m3	
reaction product: bisphenol-A-(epichlorhydrin) 25068-38-6	General population	inhalation	Long term exposure - systemic effects		0,75 mg/m3	
1,4-Bis(2,3-epoxypropoxy)butane 2425-79-8	Workers	inhalation	Long term exposure - systemic effects		4,7 mg/m3	
1,4-Bis(2,3-epoxypropoxy)butane 2425-79-8	Workers	dermal	Long term exposure - systemic effects		6,66 mg/kg	
1,4-Bis(2,3-epoxypropoxy)butane 2425-79-8	General population	inhalation	Long term exposure - systemic effects		1,16 mg/m3	
1,4-Bis(2,3-epoxypropoxy)butane 2425-79-8	General population	dermal	Long term exposure - systemic effects		3,33 mg/kg	
1,4-Bis(2,3-epoxypropoxy)butane 2425-79-8	General population	oral	Long term exposure - systemic effects		0,33 mg/kg	

**Biological Exposure Indices:**

None

**8.2. Exposure controls:**

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

**Hand protection:**

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR;  $\geq 0.4$  mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR;  $\geq 0.4$  mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

**Eye protection:**

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

**Skin protection:**

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

**Advices to personal protection equipment:**

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

## SECTION 9: Physical and chemical properties

**9.1. Information on basic physical and chemical properties**

Appearance	liquid liquid white
Odor	mild
Odour threshold	No data available / Not applicable
pH	No data available / Not applicable
Melting point	No data available / Not applicable
Solidification temperature	No data available / Not applicable
Initial boiling point	> 250 °C (> 482 °F)
Flash point	> 147 °C (> 296.6 °F)
Evaporation rate	No data available / Not applicable
Flammability	No data available / Not applicable
Explosive limits	No data available / Not applicable
Vapour pressure (50 °C (122 °F))	< 700 mbar
Relative vapour density:	No data available / Not applicable
Density ( )	1,38 g/cm <sup>3</sup>
Bulk density	No data available / Not applicable
Solubility	No data available / Not applicable
Solubility (qualitative) (Solvent: Water)	Insoluble
Partition coefficient: n-octanol/water	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Decomposition temperature	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Oxidising properties	No data available / Not applicable

**9.2. Other information**



No data available / Not applicable

**SECTION 10: Stability and reactivity****10.1. Reactivity**

Strong oxidizing agents.

**10.2. Chemical stability**

Stable under recommended storage conditions.

**10.3. Possibility of hazardous reactions**

See section reactivity

**10.4. Conditions to avoid**

No decomposition if used according to specifications.

**10.5. Incompatible materials**

See section reactivity.

**10.6. Hazardous decomposition products**

carbon oxides.

**SECTION 11: Toxicological information****11.1. Information on toxicological effects****Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	LD50	> 2.000 mg/kg	rat	OECD Guideline 420 (Acute Oral Toxicity)
1,4-bis(2,3 epoxypropoxy)butane 2425-79-8	LD50	1.118 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Quartz (SiO <sub>2</sub> ), <1% respirable 14808-60-7	LD50	> 5.050 mg/kg	rat	not specified
Titanium dioxide 13463-67-7	LD50	> 5.000 mg/kg	rat	OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure)

**Acute dermal toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
1,4-bis(2,3 epoxypropoxy)butane 2425-79-8	LD50	1.130 mg/kg	rabbit	not specified
Quartz (SiO <sub>2</sub> ), <1% respirable 14808-60-7	LD50	> 2.000 mg/kg	not specified	not specified
Titanium dioxide 13463-67-7	LD50	≥ 10.000 mg/kg	hamster	not specified

**Acute inhalative toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Titanium dioxide 13463-67-7	LC50	> 6,82 mg/l	dust	4 h	rat	not specified

**Skin corrosion/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	moderately irritating	24 h	rabbit	Draize Test
Titanium dioxide 13463-67-7	not irritating	4 h	rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

**Serious eye damage/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
1,4-bis(2,3 epoxypropoxy)butane 2425-79-8	Category 1 (irreversible effects on the eye)		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Titanium dioxide 13463-67-7	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

**Respiratory or skin sensitization:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
1,4-bis(2,3 epoxypropoxy)butane 2425-79-8	sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Titanium dioxide 13463-67-7	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

**Germ cell mutagenicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 472 (Genetic Toxicology: Escherichia coli, Reverse Mutation Assay)
1,4-bis(2,3 epoxypropoxy)butane 2425-79-8	positive	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
1,4-bis(2,3 epoxypropoxy)butane 2425-79-8	positive	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
1,4-bis(2,3 epoxypropoxy)butane 2425-79-8	positive	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Titanium dioxide 13463-67-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Titanium dioxide 13463-67-7	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Titanium dioxide 13463-67-7	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	negative	oral: gavage		mouse	not specified
1,4-bis(2,3 epoxypropoxy)butane 2425-79-8	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Titanium dioxide 13463-67-7	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

**Carcinogenicity**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	not carcinogenic	dermal	2 y daily	mouse	male	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	not carcinogenic	oral: gavage	2 y daily	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
Titanium dioxide 13463-67-7	not carcinogenic	inhalation	24 m 6 h/d; 5 d/w	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

**Reproductive toxicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	NOAEL P >= 50 mg/kg NOAEL F1 >= 750 mg/kg NOAEL F2 >= 750 mg/kg	Two generation study	oral: gavage	rat	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)
Titanium dioxide 13463-67-7	NOAEL P > 1.000 mg/kg NOAEL F1 > 1.000 mg/kg		oral: gavage	rat	OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)

**STOT-single exposure:**

No data available.

**STOT-repeated exposure::**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	NOAEL 50 mg/kg	oral: gavage	14 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
1,4-bis(2,3 epoxypropoxy)butane 2425-79-8	NOAEL 200 mg/kg	oral: gavage	28 d daily	rat	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
Titanium dioxide 13463-67-7	NOAEL 1.000 mg/kg	oral: gavage	90 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

**Aspiration hazard:**

No data available.

## SECTION 12: Ecological information

### General ecological information:

Do not empty into drains / surface water / ground water.

### 12.1. Toxicity

#### Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq$ 700) 25068-38-6	LC50	1,75 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
1,4-bis(2,3 epoxypropoxy)butane 2425-79-8	LC50	24 mg/l	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
Quartz (SiO <sub>2</sub> ), <1% respirable 14808-60-7	LC50	> 1.000 mg/l		not specified	OECD Guideline 203 (Fish, Acute Toxicity Test)
Titanium dioxide 13463-67-7	LC50		48 h	Leuciscus idus	OECD Guideline 203 (Fish, Acute Toxicity Test)

#### Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq$ 700) 25068-38-6	EC50	1,7 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
1,4-bis(2,3 epoxypropoxy)butane 2425-79-8	EC50	75 mg/l	24 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Quartz (SiO <sub>2</sub> ), <1% respirable 14808-60-7	EC50	> 1.000 mg/l		Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Titanium dioxide 13463-67-7	EC50		48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

#### Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq$ 700) 25068-38-6	NOEC	0,3 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

#### Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	EC50	> 11 mg/l	72 h	Scenedesmus capricornutum	OECD Guideline 201 (Alga, Growth Inhibition Test)
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	NOEC	4,2 mg/l	72 h	Scenedesmus capricornutum	OECD Guideline 201 (Alga, Growth Inhibition Test)
1,4-bis(2,3 epoxypropoxy)butane 2425-79-8	EC50	> 160 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
1,4-bis(2,3 epoxypropoxy)butane 2425-79-8	EC10	97 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Quartz (SiO <sub>2</sub> ), <1% respirable 14808-60-7	EC50	> 1.000 mg/l		not specified	OECD Guideline 201 (Alga, Growth Inhibition Test)
Titanium dioxide 13463-67-7	EC50		72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)

### Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	IC50	> 100 mg/l	3 h	activated sludge, industrial	other guideline:
1,4-bis(2,3 epoxypropoxy)butane 2425-79-8	IC50	> 100 mg/l	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Quartz (SiO <sub>2</sub> ), <1% respirable 14808-60-7	EC0	> 1.000 mg/l		not specified	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Titanium dioxide 13463-67-7	EC0		24 h	Pseudomonas fluorescens	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm- Test)

### 12.2. Persistence and degradability

The product is not biodegradable.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	not readily biodegradable.	aerobic	5 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
1,4-bis(2,3 epoxypropoxy)butane 2425-79-8	not readily biodegradable.	aerobic	38 %	28 d	OECD Guideline 301 E (Ready biodegradability: Modified OECD Screening Test)

### 12.3. Bioaccumulative potential

No data available.

### 12.4. Mobility in soil

Cured adhesives are immobile.

Hazardous substances CAS-No.	LogPow	Temperature	Method
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	3,242	25 °C	EU Method A.8 (Partition Coefficient)
1,4-bis(2,3 epoxypropoxy)butane 2425-79-8	-0,269	25 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)

### 12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
1,4-bis(2,3 epoxypropoxy)butane 2425-79-8	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Quartz (SiO <sub>2</sub> ), <1% respirable 14808-60-7	According to Annex XIII of regulation (EC) 1907/2006 a PBT and vPvB assessment shall not be conducted for inorganic substances.
Titanium dioxide 13463-67-7	According to Annex XIII of regulation (EC) 1907/2006 a PBT and vPvB assessment shall not be conducted for inorganic substances.

### 12.6. Other adverse effects

No data available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product disposal:

Dispose of in accordance with local and national regulations.

Do not empty into drains / surface water / ground water.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

## SECTION 14: Transport information

**14.1. UN number**

ADR	3082
RID	3082
ADN	3082
IMDG	3082
IATA	3082

**14.2. UN proper shipping name**

ADR	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-A Epichlorhydrin resin)
RID	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-A Epichlorhydrin resin)
ADN	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-A Epichlorhydrin resin)
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-A Epichlorhydrin resin)
IATA	Environmentally hazardous substance, liquid, n.o.s. (Bisphenol-A Epichlorhydrin resin)

**14.3. Transport hazard class(es)**

ADR	9
RID	9
ADN	9
IMDG	9
IATA	9

**14.4. Packing group**

ADR	III
RID	III
ADN	III
IMDG	III
IATA	III

**14.5. Environmental hazards**

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	Marine pollutant
IATA	not applicable

**14.6. Special precautions for user**

ADR	not applicable Tunnelcode:
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

The transport classifications in this section apply generally to packed and bulk goods alike. For containers with a net volume of no more than 5 L for liquid substances or a net mass of no more than 5 kg for solid substances per individual or inner package, the exemptions SP 375 (ADR), 197 (IATA), 969 (IMDG) may be applied, which can result in a deviation from the transport classification for packed goods.

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

not applicable



**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

VOC content < 3,00 %  
(2010/75/EC)

**15.2. Chemical safety assessment**

A chemical safety assessment has not been carried out.

**SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H302 Harmful if swallowed.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H411 Toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.

**Further information:**

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your\_company.com).

**Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.**



## Safety Data Sheet according to (EC) No 1907/2006 as amendedPage 1 of 23

LOCTITE EA 9480 DC50ML EN/DE

SDS No. : 282495

V003.0

Revision: 03.07.2020

printing date: 04.07.2020

Replaces version from: 29.05.2020

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

LOCTITE EA 9480 DC50ML EN/DE

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Epoxy Hardener

#### 1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Adhesives

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

Fax-no.: +44 (1442) 278071

ua-productsafety.uk@henkel.com

#### 1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

### SECTION 2: Hazards identification


#### 2.1. Classification of the substance or mixture

##### Classification (CLP):

Acute toxicity	Category 4
H302 Harmful if swallowed.	
Route of Exposure: Oral	
Acute toxicity	Category 4
H332 Harmful if inhaled.	
Route of Exposure: Inhalation	
Skin corrosion	Sub-category 1B
H314 Causes severe skin burns and eye damage.	
Serious eye damage	Category 1
H318 Causes serious eye damage.	
Skin sensitizer	Category 1
H317 May cause an allergic skin reaction.	
Toxic to reproduction	Category 1B
H360F May damage fertility.	
Acute hazards to the aquatic environment	Category 1
H400 Very toxic to aquatic life.	
Chronic hazards to the aquatic environment	Category 1
H410 Very toxic to aquatic life with long lasting effects.	

## 2.2. Label elements

### Label elements (CLP):

<b>Hazard pictogram:</b>	
<b>Contains</b>	<p>Fatty acids, tall-oil, reaction products with diethylenetriamine</p> <p>Diethylenetriamine 4,4'-Isopropylidenediphenol</p> <p>4,4'-Isopropylidenediphenol, polymer with 1-chloro-2,3-epoxypropane, reaction products with diethylenetriamine</p> <p>Fatty acids, C18-unsatd., dimers, polymeric reaction products with tall-oil fatty acids and diethylenetriamine</p>
<b>Signal word:</b>	Danger
<b>Hazard statement:</b>	<p>H302+H332 Harmful if swallowed or if inhaled.</p> <p>H314 Causes severe skin burns and eye damage.</p> <p>H317 May cause an allergic skin reaction.</p> <p>H360F May damage fertility.</p> <p>H410 Very toxic to aquatic life with long lasting effects.</p>
<b>Supplemental information</b>	<p>EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.</p> <p>Restricted to professional users.</p>
<b>Precautionary statement: Prevention</b>	<p>P201 Obtain special instructions before use.</p> <p>P261 Avoid breathing vapors.</p> <p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves/protective clothing/eye protection/face protection.</p>
<b>Precautionary statement: Response</b>	<p>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P308+P313 IF exposed or concerned: Get medical advice/attention.</p> <p>P310 Immediately call a POISON CENTER or doctor.</p>

## 2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

**Declaration of the ingredients according to CLP (EC) No 1272/2008:**

<b>Hazardous components CAS-No.</b>	<b>EC Number REACH-Reg No.</b>	<b>content</b>	<b>Classification</b>
Fatty acids, tall-oil, reaction products with diethylenetriamine 61790-69-0	263-160-2	25- 50 %	Skin Corr. 1B H314 Acute Tox. 4; Oral H302 Aquatic Acute 1 H400 Aquatic Chronic 1 H410
Diethylenetriamine 111-40-0	203-865-4 01-2119473793-27	1- < 5 %	Acute Tox. 4; Oral H302 Acute Tox. 4; Dermal H312 Skin Corr. 1B H314 Skin Sens. 1 H317 Acute Tox. 2; Inhalation H330 STOT SE 3 H335 Eye Dam. 1 H318
4-tert-butylphenol 98-54-4	202-679-0 01-2119489419-21	1- < 3 %	Aquatic Chronic 1 H410 Repr. 2 H361f Skin Irrit. 2 H315 Eye Dam. 1 H318 ===== EU. REACH Candidate List of Substances of Very High Concern for Authorization (SVHC)
4,4'-Isopropylidenediphenol 80-05-7	201-245-8 01-2119457856-23	1- < 3 %	Aquatic Chronic 2 H411 Eye Dam. 1 H318 Skin Sens. 1 H317 STOT SE 3 H335 Repr. 1B H360F ===== EU. REACH Candidate List of Substances of Very High Concern for Authorization (SVHC) EU. REACH Candidate List of Substances of Very High Concern for Authorization (SVHC)
Titanium dioxide 13463-67-7	236-675-5 01-2119489379-17	1- < 5 %	
Quartz (SiO <sub>2</sub> ), <1% respirable 14808-60-7	238-878-4	1- < 5 %	
benzyl alcohol 100-51-6	202-859-9 01-2119492630-38	1- < 5 %	Acute Tox. 4; Oral H302 Acute Tox. 4; Inhalation H332 Eye Irrit. 2 H319
4,4'-Isopropylidenediphenol, polymer with 1-chloro-2,3-epoxypropane, reaction products with diethylenetriamine 31326-29-1	500-072-8	0,1- < 1 %	Acute Tox. 4; Oral H302 Acute Tox. 4; Dermal H312 Skin Corr. 1B H314

			Skin Sens. 1 H317
Fatty acids, C18-unsatd., dimers, polymeric reaction products with tall-oil fatty acids and diethylenetriamine		0,1- < 1 %	Skin Irrit. 2 H315 Eye Irrit. 2 H319 Skin Sens. 1A H317

**For full text of the H - statements and other abbreviations see section 16 "Other information".**  
**Substances without classification may have community workplace exposure limits available.**

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

Causes burns.

SKIN: Rash, Urticaria.

INGESTION: Nausea, vomiting, diarrhea, abdominal pain.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

### 4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

**Suitable extinguishing media:**

Carbon dioxide, foam, powder

**Extinguishing media which must not be used for safety reasons:**

None known

### 5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and nitrogen oxides (NO<sub>x</sub>) can be released.

### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

**Additional information:**

In case of fire, keep containers cool with water spray.

## SECTION 6: Accidental release measures

**6.1. Personal precautions, protective equipment and emergency procedures**

Avoid contact with skin and eyes.  
Ensure adequate ventilation.  
Wear protective equipment.

**6.2. Environmental precautions**

Do not empty into drains / surface water / ground water.

**6.3. Methods and material for containment and cleaning up**

For small spills wipe up with paper towel and place in container for disposal.  
For large spills absorb onto inert absorbent material and place in sealed container for disposal.  
Wash spillage site thoroughly with soap and water or detergent solution.  
Dispose of contaminated material as waste according to Section 13.

**6.4. Reference to other sections**

See advice in section 8

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

Use only in well-ventilated areas.  
Avoid skin and eye contact.  
Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.  
See advice in section 8

Hygiene measures:

Wash hands before work breaks and after finishing work.  
Do not eat, drink or smoke while working.  
Good industrial hygiene practices should be observed.

**7.2. Conditions for safe storage, including any incompatibilities**

Store in a cool, well-ventilated place.  
Refer to Technical Data Sheet

**7.3. Specific end use(s)**

Epoxy Hardener

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational Exposure Limits

Valid for  
Great Britain

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Kaolin 1332-58-7 [KAOLIN, RESPIRABLE DUST]		2	Time Weighted Average (TWA):		EH40 WEL
Mica 12001-26-2 [MICA, RESPIRABLE]		0,8	Time Weighted Average (TWA):		EH40 WEL
Mica 12001-26-2 [MICA, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		EH40 WEL
2,2'-Iminodi(ethylamine) 111-40-0 [2,2'-IMINODI(ETHYLAMINE)]			Skin designation:	Can be absorbed through the skin.	EH40 WEL
2,2'-Iminodi(ethylamine) 111-40-0 [2,2'-IMINODI(ETHYLAMINE)]	1	4,3	Time Weighted Average (TWA):		EH40 WEL
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		EH40 WEL
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE, RESPIRABLE]		4	Time Weighted Average (TWA):		EH40 WEL
4,4'-Isopropylidenediphenol 80-05-7 [BISPHENOL A]		2	Time Weighted Average (TWA):		EH40 WEL
4,4'-Isopropylidenediphenol 80-05-7 [BISPHENOL A (4,4'-ISOPROPYLIDENEDIPHENOL) (INHALABLE FRACTION)]		2	Time Weighted Average (TWA):	Indicative	ECTLV
Quartz (SiO <sub>2</sub> ) 14808-60-7 [SILICA, RESPIRABLE CRYSTALLINE]		0,1	Time Weighted Average (TWA):		EH40 WEL
Quartz (SiO <sub>2</sub> ) 14808-60-7 [RESPIRABLE CRYSTALLINE SILICA DUST]		0,1	Time Weighted Average (TWA):		EU OELIII

#### Occupational Exposure Limits

Valid for  
Ireland

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Kaolin 1332-58-7 [KAOLIN, RESPIRABLE DUST]		2	Time Weighted Average (TWA):		IR_OEL
Mica 12001-26-2 [MICA (RESPIRABLE FRACTION)]		3	Time Weighted Average (TWA):		IR_OEL
2,2'-Iminodi(ethylamine) 111-40-0 [DIETHYLENE TRIAMINE]	1	4	Time Weighted Average (TWA):		IR_OEL
2,2'-Iminodi(ethylamine) 111-40-0 [DIETHYLENE TRIAMINE]			Skin designation:	Can be absorbed through the skin.	IR_OEL
Titanium dioxide 13463-67-7		4	Time Weighted Average (TWA):		IR_OEL

[TITANIUM DIOXIDE, RESPIRABLE DUST]					
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE, TOTAL INHALABLE DUST]		10	Time Weighted Average (TWA):		IR_OEL
4,4'-Isopropylidenediphenol 80-05-7 [BISPHENOL A (4,4'-ISOPROPYLIDENEDIPHENOL) (INHALABLE DUST)]		2	Time Weighted Average (TWA):	Indicative OELV	IR_OEL
4,4'-Isopropylidenediphenol 80-05-7 [BISPHENOL A (4,4'-ISOPROPYLIDENEDIPHENOL) (INHALABLE FRACTION)]		2	Time Weighted Average (TWA):	Indicative	ECLTV
Quartz (SiO <sub>2</sub> ) 14808-60-7 [QUARTZ, RESPIRABLE DUST (SEE CRYSTALLINE SILICA)]		0,1	Time Weighted Average (TWA):		IR_OEL
Quartz (SiO <sub>2</sub> ) 14808-60-7 [RESPIRABLE CRYSTALLINE SILICA DUST]		0,1	Time Weighted Average (TWA):		EU OELIII



**Predicted No-Effect Concentration (PNEC):**

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
2,2'-iminodiethylamine 111-40-0	aqua (freshwater)		0,56 mg/l				
2,2'-iminodiethylamine 111-40-0	aqua (marine water)		0,056 mg/l				
2,2'-iminodiethylamine 111-40-0	aqua (intermittent releases)		0,32 mg/l				
2,2'-iminodiethylamine 111-40-0	sediment (freshwater)				1072 mg/kg		
2,2'-iminodiethylamine 111-40-0	sediment (marine water)				107,2 mg/kg		
2,2'-iminodiethylamine 111-40-0	sewage treatment plant (STP)		6 mg/l				
2,2'-iminodiethylamine 111-40-0	Soil				7,97 mg/kg		
2,2'-iminodiethylamine 111-40-0	Air						no hazard identified
4-tert-butylphenol 98-54-4	aqua (marine water)		0,001 mg/l				
4-tert-butylphenol 98-54-4	aqua (freshwater)		0,01 mg/l				
4-tert-butylphenol 98-54-4	aqua (intermittent releases)		0,048 mg/l				
4-tert-butylphenol 98-54-4	sediment (marine water)				0,027 mg/kg		
4-tert-butylphenol 98-54-4	sediment (freshwater)				0,27 mg/kg		
4-tert-butylphenol 98-54-4	sewage treatment plant (STP)		1,5 mg/l				
4-tert-butylphenol 98-54-4	Soil				0,25 mg/kg		
4-tert-butylphenol 98-54-4	oral				46,67 mg/kg		
4,4'-Isopropylidenediphenol 80-05-7	aqua (freshwater)		0,018 mg/l				
4,4'-Isopropylidenediphenol 80-05-7	aqua (marine water)		0,018 mg/l				
4,4'-Isopropylidenediphenol 80-05-7	aqua (intermittent releases)		0,011 mg/l				
4,4'-Isopropylidenediphenol 80-05-7	sewage treatment plant (STP)		320 mg/l				
4,4'-Isopropylidenediphenol 80-05-7	sediment (freshwater)				1,2 mg/kg		
4,4'-Isopropylidenediphenol 80-05-7	sediment (marine water)				0,24 mg/kg		
4,4'-Isopropylidenediphenol 80-05-7	Soil				3,7 mg/kg		
4,4'-Isopropylidenediphenol 80-05-7	Air						no hazard identified
4,4'-Isopropylidenediphenol 80-05-7	Predator						no potential for bioaccumulation
Titanium dioxide 13463-67-7	aqua (freshwater)						no hazard identified
Titanium dioxide 13463-67-7	aqua (marine water)						no hazard identified
Titanium dioxide 13463-67-7	sewage treatment plant (STP)						no hazard identified
Titanium dioxide 13463-67-7	sediment (freshwater)						no hazard identified
Titanium dioxide 13463-67-7	sediment (marine water)						no hazard identified

Titanium dioxide 13463-67-7	Soil						no hazard identified
Titanium dioxide 13463-67-7	Aquatic (intermit. releases)						no hazard identified
Titanium dioxide 13463-67-7	Predator						no hazard identified
Benzyl alcohol 100-51-6	Soil				0,456 mg/kg		
Benzyl alcohol 100-51-6	sewage treatment plant (STP)		39 mg/l				
Benzyl alcohol 100-51-6	sediment (freshwater)				5,27 mg/kg		
Benzyl alcohol 100-51-6	sediment (marine water)				0,527 mg/kg		
Benzyl alcohol 100-51-6	aqua (marine water)		0,1 mg/l				
Benzyl alcohol 100-51-6	aqua (intermittent releases)		2,3 mg/l				
Benzyl alcohol 100-51-6	aqua (freshwater)		1 mg/l				
Benzyl alcohol 100-51-6	Air						no hazard identified
Benzyl alcohol 100-51-6	Predator						no potential for bioaccumulation

**Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
2,2'-iminodiethylamine 111-40-0	Workers	dermal	Long term exposure - systemic effects		11,4 mg/kg	no hazard identified
2,2'-iminodiethylamine 111-40-0	Workers	dermal	Long term exposure - local effects		1,1 mg/kg	no hazard identified
2,2'-iminodiethylamine 111-40-0	Workers	Inhalation	Acute/short term exposure - systemic effects		92,1 mg/m <sup>3</sup>	no hazard identified
2,2'-iminodiethylamine 111-40-0	Workers	Inhalation	Acute/short term exposure - local effects		2,6 mg/m <sup>3</sup>	no hazard identified
2,2'-iminodiethylamine 111-40-0	Workers	Inhalation	Long term exposure - systemic effects		15,4 mg/m <sup>3</sup>	no hazard identified
2,2'-iminodiethylamine 111-40-0	Workers	Inhalation	Long term exposure - local effects		0,87 mg/m <sup>3</sup>	no hazard identified
2,2'-iminodiethylamine 111-40-0	General population	dermal	Acute/short term exposure - systemic effects		4,88 mg/kg	no hazard identified
2,2'-iminodiethylamine 111-40-0	General population	Inhalation	Acute/short term exposure - systemic effects		27,5 mg/m <sup>3</sup>	no hazard identified
2,2'-iminodiethylamine 111-40-0	General population	dermal	Long term exposure - systemic effects		4,88 mg/kg	no hazard identified
2,2'-iminodiethylamine 111-40-0	General population	Inhalation	Long term exposure - systemic effects		4,6 mg/m <sup>3</sup>	no hazard identified
4-tert-butylphenol 98-54-4	General population	dermal	Long term exposure - systemic effects		0,026 mg/kg	
4-tert-butylphenol 98-54-4	General population	inhalation	Long term exposure - systemic effects		0,09 mg/m <sup>3</sup>	
4-tert-butylphenol 98-54-4	General population	oral	Long term exposure - systemic effects		0,026 mg/kg	
4-tert-butylphenol 98-54-4	Workers	dermal	Long term exposure - systemic effects		0,071 mg/kg	
4-tert-butylphenol 98-54-4	Workers	inhalation	Long term exposure - systemic effects		0,5 mg/m <sup>3</sup>	
4,4'-Isopropylidenediphenol 80-05-7	Workers	dermal	Acute/short term exposure - systemic effects		0,031 mg/kg	no hazard identified
4,4'-Isopropylidenediphenol 80-05-7	Workers	dermal	Long term exposure - systemic effects		0,031 mg/kg	no hazard identified
4,4'-Isopropylidenediphenol 80-05-7	Workers	Inhalation	Acute/short term exposure - systemic effects		2 mg/m <sup>3</sup>	no hazard identified
4,4'-Isopropylidenediphenol 80-05-7	Workers	Inhalation	Long term exposure - systemic effects		2 mg/m <sup>3</sup>	no hazard identified
4,4'-Isopropylidenediphenol 80-05-7	General population	dermal	Long term exposure - systemic effects		0,002 mg/kg	no hazard identified
4,4'-Isopropylidenediphenol 80-05-7	General population	Inhalation	Long term exposure - systemic effects		1 mg/m <sup>3</sup>	no hazard identified
4,4'-Isopropylidenediphenol 80-05-7	Workers	inhalation	Long term exposure - local effects		2 mg/m <sup>3</sup>	no hazard identified
4,4'-Isopropylidenediphenol 80-05-7	Workers	inhalation	Acute/short term exposure - local		2 mg/m <sup>3</sup>	no hazard identified

			effects			
4,4'-Isopropylidenediphenol 80-05-7	General population	inhalation	Acute/short term exposure - systemic effects		1 mg/m <sup>3</sup>	no hazard identified
4,4'-Isopropylidenediphenol 80-05-7	General population	inhalation	Long term exposure - local effects		1 mg/m <sup>3</sup>	no hazard identified
4,4'-Isopropylidenediphenol 80-05-7	General population	inhalation	Acute/short term exposure - local effects		1 mg/m <sup>3</sup>	no hazard identified
4,4'-Isopropylidenediphenol 80-05-7	General population	dermal	Acute/short term exposure - systemic effects		0,002 mg/kg	no hazard identified
4,4'-Isopropylidenediphenol 80-05-7	General population	oral	Long term exposure - systemic effects		0,004 mg/kg	no hazard identified
4,4'-Isopropylidenediphenol 80-05-7	General population	oral	Acute/short term exposure - systemic effects		0,004 mg/kg	no hazard identified
Benzyl alcohol 100-51-6	General population	oral	Acute/short term exposure - systemic effects		20 mg/kg	no hazard identified
Benzyl alcohol 100-51-6	General population	oral	Long term exposure - systemic effects		4 mg/kg	no hazard identified
Benzyl alcohol 100-51-6	Workers	inhalation	Acute/short term exposure - systemic effects		110 mg/m <sup>3</sup>	no hazard identified
Benzyl alcohol 100-51-6	Workers	inhalation	Long term exposure - systemic effects		22 mg/m <sup>3</sup>	no hazard identified
Benzyl alcohol 100-51-6	General population	inhalation	Acute/short term exposure - systemic effects		27 mg/m <sup>3</sup>	no hazard identified
Benzyl alcohol 100-51-6	General population	inhalation	Long term exposure - systemic effects		5,4 mg/m <sup>3</sup>	no hazard identified
Benzyl alcohol 100-51-6	Workers	dermal	Acute/short term exposure - systemic effects		40 mg/kg	no hazard identified
Benzyl alcohol 100-51-6	Workers	dermal	Long term exposure - systemic effects		8 mg/kg	no hazard identified
Benzyl alcohol 100-51-6	General population	dermal	Acute/short term exposure - systemic effects		20 mg/kg	no hazard identified
Benzyl alcohol 100-51-6	General population	dermal	Long term exposure - systemic effects		4 mg/kg	no hazard identified

**Biological Exposure Indices:**

None

**8.2. Exposure controls:**

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

**Hand protection:**

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR;  $\geq 0.4$  mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR;  $\geq 0.4$  mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

**Eye protection:**

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

**Skin protection:**

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

**Advices to personal protection equipment:**

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

## SECTION 9: Physical and chemical properties

**9.1. Information on basic physical and chemical properties**

Appearance	liquid
	liquid
	white
Odor	ammoniacal
Odour threshold	No data available / Not applicable
pH	No data available / Not applicable
Melting point	No data available / Not applicable
Solidification temperature	No data available / Not applicable
Initial boiling point	180 °C (356 °F)
Flash point	130 °C (266 °F)
Evaporation rate	No data available / Not applicable
Flammability	No data available / Not applicable
Explosive limits	No data available / Not applicable
Vapour pressure	No data available / Not applicable
Relative vapour density:	No data available / Not applicable
Density	1,32 g/cm <sup>3</sup>
( )	
Bulk density	No data available / Not applicable
Solubility	No data available / Not applicable
Solubility (qualitative)	No data available / Not applicable
Partition coefficient: n-octanol/water	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Decomposition temperature	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Oxidising properties	No data available / Not applicable

**9.2. Other information**

No data available / Not applicable

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reaction with strong acids.

Reacts with strong oxidants.

### 10.2. Chemical stability

Stable under recommended storage conditions.

### 10.3. Possibility of hazardous reactions

See section reactivity

### 10.4. Conditions to avoid

Stable under normal conditions of storage and use.

### 10.5. Incompatible materials

See section reactivity.

### 10.6. Hazardous decomposition products

carbon oxides.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Diethylenetriamine 111-40-0	LD50	1.553 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
4-tert-butylphenol 98-54-4	LD50	4.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
4,4'- Isopropylidenediphenol 80-05-7	LD50	> 2.000 - < 5.000 mg/kg		
4,4'- Isopropylidenediphenol 80-05-7	Acute toxicity estimate (ATE)	2.500 mg/kg		Expert judgement
Titanium dioxide 13463-67-7	LD50	> 5.000 mg/kg	rat	OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure)
Quartz (SiO <sub>2</sub> ), <1% respirable 14808-60-7	LD50	> 5.050 mg/kg	rat	not specified
benzyl alcohol 100-51-6	LD50	1.620 mg/kg	rat	not specified
4,4'- Isopropylidenediphenol, polymer with 1-chloro- 2,3-epoxypropane, reaction products with diethylenetriamine 31326-29-1	LD50	1.140 mg/kg	rat	not specified

**Acute dermal toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Diethylenetriamine 111-40-0	LD50	1.045 mg/kg	rabbit	not specified
4-tert-butylphenol 98-54-4	LD50	> 16.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
4,4'- Isopropylidenediphenol 80-05-7	LD50	3.600 mg/kg	rabbit	not specified
Titanium dioxide 13463-67-7	LD50	>= 10.000 mg/kg	hamster	not specified
Quartz (SiO <sub>2</sub> ), <1% respirable 14808-60-7	LD50	> 2.000 mg/kg	not specified	not specified
benzyl alcohol 100-51-6	Acute toxicity estimate (ATE)	2.500 mg/kg		Expert judgement

**Acute inhalative toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Diethylenetriamine 111-40-0	NOEL	0,07 mg/l			rat	OECD Guideline 403 (Acute Inhalation Toxicity)
Diethylenetriamine 111-40-0	Acute toxicity estimate (ATE)	0,07 mg/l	dust/mist			Expert judgement
Titanium dioxide 13463-67-7	LC50	> 6,82 mg/l	dust	4 h	rat	not specified
benzyl alcohol 100-51-6	Acute toxicity estimate (ATE)	4,17 mg/l	dust/mist			Expert judgement
benzyl alcohol 100-51-6	LC50	> 4,178 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)

**Skin corrosion/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Diethylenetriamine 111-40-0	corrosive	15 min	rabbit	BASF Test
4-tert-butylphenol 98-54-4	irritating	5 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Titanium dioxide 13463-67-7	not irritating	4 h	rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
benzyl alcohol 100-51-6	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

**Serious eye damage/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Diethylenetriamine 111-40-0	corrosive	30 s	rabbit	not specified
4-tert-butylphenol 98-54-4	Category 1 (irreversible effects on the eye)	1 s	rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Titanium dioxide 13463-67-7	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
benzyl alcohol 100-51-6	irritating	24 h	rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

**Respiratory or skin sensitization:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Diethylenetriamine 111-40-0	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
4-tert-butylphenol 98-54-4	sensitising			not specified
4,4'- Isopropylidenediphenol 80-05-7	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 406 (Skin Sensitisation)
Titanium dioxide 13463-67-7	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
benzyl alcohol 100-51-6	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

**Germ cell mutagenicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Diethylenetriamine 111-40-0	positive	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Diethylenetriamine 111-40-0	negative	in vitro mammalian chromosome aberration test	with and without		Chromosome Aberration Test
4-tert-butylphenol 98-54-4	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
4,4'- Isopropylidenediphenol 80-05-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		not specified
Titanium dioxide 13463-67-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Titanium dioxide 13463-67-7	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Titanium dioxide 13463-67-7	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
benzyl alcohol 100-51-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)



**Carcinogenicity**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Diethylenetriamine 111-40-0	not carcinogenic	dermal	lifetime (appr. 587 d) 3 d/w	mouse	male	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
Titanium dioxide 13463-67-7	not carcinogenic	inhalation	24 m 6 h/d; 5 d/w	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
benzyl alcohol 100-51-6	not carcinogenic	oral: gavage	104 weeks once daily, 5 days/week	rat	male/female	equivalent or similar OECD Guideline 451 (Carcinogenicity Studies)

**Reproductive toxicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Diethylenetriamine 111-40-0	NOAEL P 100 mg/kg NOAEL F1 30 mg/kg	screening	oral: gavage	rat	OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)
4,4'- Isopropylidenediphenol 80-05-7	NOAEL P 300 ppm		oral: feed	mouse	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)
Titanium dioxide 13463-67-7	NOAEL P > 1.000 mg/kg NOAEL F1 > 1.000 mg/kg		oral: gavage	rat	OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)
benzyl alcohol 100-51-6	NOAEL P 200 mg/kg	screening	oral: gavage	mouse	not specified

**STOT-single exposure:**

No data available.

**STOT-repeated exposure::**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Diethylenetriamine 111-40-0	NOAEL 70 - 80 mg/kg	oral: feed	90 d daily	rat	not specified
Diethylenetriamine 111-40-0	NOAEL 0,55 mg/l	inhalation: vapour	15 d 6 h/d	rat	not specified
4-tert-butylphenol 98-54-4	LOAEL >= 200 mg/kg	oral: gavage	daily	rat	not specified
Titanium dioxide 13463-67-7	NOAEL 1.000 mg/kg	oral: gavage	90 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
benzyl alcohol 100-51-6	NOAEL 400 mg/kg	oral: gavage	13 weeks once daily, 5 days/week	rat	equivalent or similar to OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

**Aspiration hazard:**

No data available.

## SECTION 12: Ecological information

### General ecological information:

Do not empty into drains / surface water / ground water.

### 12.1. Toxicity

#### Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Fatty acids, tall-oil, reaction products with diethylenetriamine 61790-69-0	LC50	0,63 mg/l	96 h	Salmo gairdneri (new name: Oncorhynchus mykiss)	OECD Guideline 203 (Fish, Acute Toxicity Test)
Diethylenetriamine 111-40-0	LC50	430 mg/l	96 h	Poecilia reticulata	EU Method C.1 (Acute Toxicity for Fish)
Diethylenetriamine 111-40-0	NOEC	> 10 mg/l	28 d	Gasterosteus aculeatus	OECD Guideline 210 (fish early life stage toxicity test)
4-tert-butylphenol 98-54-4	LC50	5,14 mg/l	96 h	Pimephales promelas	EU Method C.1 (Acute Toxicity for Fish)
4-tert-butylphenol 98-54-4	NOEC	> 0,01 - 0,1 mg/l	128 d	Pimephales promelas	OECD Guideline 210 (fish early life stage toxicity test)
4,4'-Isopropylidenediphenol 80-05-7	LC50	4,6 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
4,4'-Isopropylidenediphenol 80-05-7	NOEC	0,016 mg/l	444 d	Pimephales promelas	EPA OPP 72-5 (Fish Life Cycle Toxicity)
Titanium dioxide 13463-67-7	LC50		48 h	Leuciscus idus	OECD Guideline 203 (Fish, Acute Toxicity Test)
Quartz (SiO <sub>2</sub> ), <1% respirable 14808-60-7	LC50	> 1.000 mg/l		not specified	OECD Guideline 203 (Fish, Acute Toxicity Test)
benzyl alcohol 100-51-6	LC50	460 mg/l	96 h	Pimephales promelas	EPA OPP 72-1 (Fish Acute Toxicity Test)

#### Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Diethylenetriamine 111-40-0	EC50	64,6 mg/l	48 h	Daphnia magna	EU Method C.2 (Acute Toxicity for Daphnia)
4-tert-butylphenol 98-54-4	EC50	4,8 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
4,4'-Isopropylidenediphenol 80-05-7	EC50	3,9 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Titanium dioxide 13463-67-7	EC50		48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Quartz (SiO <sub>2</sub> ), <1% respirable 14808-60-7	EC50	> 1.000 mg/l		Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
benzyl alcohol 100-51-6	EC50	230 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

#### Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Diethylenetriamine 111-40-0	NOEC	5,6 mg/l	21 d	Daphnia magna	EU Method C.20 (Daphnia magna Reproduction Test)
4-tert-butylphenol 98-54-4	NOEC	0,73 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
4,4'-Isopropylidenediphenol	NOEC	0,17 mg/l	28 d	Americamysis bahia	EPA OPPTS 850.1350

80-05-7					(Mysid Chronic Toxicity Test)
benzyl alcohol 100-51-6	NOEC	51 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

**Toxicity (Algae):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Diethylenetriamine 111-40-0	EC50	1.164 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Diethylenetriamine 111-40-0	NOEC	10 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
4-tert-butylphenol 98-54-4	EC50	11,2 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	DIN 38412-09
4-tert-butylphenol 98-54-4	NOEC	0,32 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	DIN 38412-09
4,4'-Isopropylidenediphenol 80-05-7	EC50	> 2,73 - 3,1 mg/l	96 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
4,4'-Isopropylidenediphenol 80-05-7	EC10	1,36 mg/l	96 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Titanium dioxide 13463-67-7	EC50		72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Quartz (SiO <sub>2</sub> ), <1% respirable 14808-60-7	EC50	> 1.000 mg/l		not specified	OECD Guideline 201 (Alga, Growth Inhibition Test)
benzyl alcohol 100-51-6	EC50	770 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
benzyl alcohol 100-51-6	NOEC	310 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)

**Toxicity to microorganisms**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Fatty acids, tall-oil, reaction products with diethylenetriamine 61790-69-0	EC0	10 mg/l	30 min		not specified
Diethylenetriamine 111-40-0	NOEC	6 mg/l	3 h	anaerobic bacteria	not specified
4-tert-butylphenol 98-54-4	EC50	> 10 mg/l	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
4,4'-Isopropylidenediphenol 80-05-7	EC10	> 320 mg/l	18 h	Pseudomonas putida	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm-Test)
Titanium dioxide 13463-67-7	EC0		24 h	Pseudomonas fluorescens	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm-Test)
Quartz (SiO <sub>2</sub> ), <1% respirable 14808-60-7	EC0	> 1.000 mg/l		not specified	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
benzyl alcohol 100-51-6	EC10	658 mg/l	17 h	Pseudomonas putida	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm-Test)

**12.2. Persistence and degradability**

The product is not biodegradable.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Fatty acids, tall-oil, reaction products with diethylenetriamine 61790-69-0		aerobic	21 %	28 d	ISO 10708 (BODIS-Test)
Diethylenetriamine 111-40-0	inherently biodegradable	aerobic	83 %	28 d	EU Method C.9 (Biodegradation: Zahn-Wellens Test)
Diethylenetriamine 111-40-0	readily biodegradable	aerobic	87 %	21 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
4-tert-butylphenol 98-54-4	readily biodegradable	aerobic	98 %	28 d	OECD Guideline 301 A (new version) (Ready Biodegradability: DOC Die Away Test)
4,4'-Isopropylidenediphenol 80-05-7	readily biodegradable	aerobic	89 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
benzyl alcohol 100-51-6	readily biodegradable	aerobic	92 - 96 %	14 d	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))

**12.3. Bioaccumulative potential**

Hazardous substances CAS-No.	Bioconcentration factor (BCF)	Exposure time	Temperature	Species	Method
Diethylenetriamine 111-40-0	> 0,3 - < 6,3	42 d		Cyprinus carpio	OECD Guideline 305 C (Bioaccumulation: Test for the Degree of Bioconcentration in Fish)
4-tert-butylphenol 98-54-4	20 - 48	56 d		Cyprinus carpio	OECD Guideline 305 C (Bioaccumulation: Test for the Degree of Bioconcentration in Fish)
4,4'-Isopropylidenediphenol 80-05-7	5,1 - 67	42 d	25 °C	Cyprinus carpio	other guideline:

**12.4. Mobility in soil**

Cured adhesives are immobile.

Hazardous substances CAS-No.	LogPow	Temperature	Method
Diethylenetriamine 111-40-0	-1,58	20 °C	QSAR (Quantitative Structure Activity Relationship)
4-tert-butylphenol 98-54-4	3	23 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
4,4'-Isopropylidenediphenol 80-05-7	3,4	21,5 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
benzyl alcohol 100-51-6	1,05	20 °C	EU Method A.8 (Partition Coefficient)

### 12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
Fatty acids, tall-oil, reaction products with diethylenetriamine 61790-69-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Diethylenetriamine 111-40-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
4-tert-butylphenol 98-54-4	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
4,4'-Isopropylidenediphenol 80-05-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Titanium dioxide 13463-67-7	According to Annex XIII of regulation (EC) 1907/2006 a PBT and vPvB assessment shall not be conducted for inorganic substances.
Quartz (SiO <sub>2</sub> ), <1% respirable 14808-60-7	According to Annex XIII of regulation (EC) 1907/2006 a PBT and vPvB assessment shall not be conducted for inorganic substances.
benzyl alcohol 100-51-6	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Fatty acids, C18-unsatd., dimers, polymeric reaction products with tall-oil fatty acids and diethylenetriamine	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

### 12.6. Other adverse effects

No data available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product disposal:

Dispose of in accordance with local and national regulations.

Do not empty into drains / surface water / ground water.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

## SECTION 14: Transport information

### 14.1. UN number

ADR	2735
RID	2735
ADN	2735
IMDG	2735
IATA	2735

### 14.2. UN proper shipping name

ADR	AMINES, LIQUID, CORROSIVE, N.O.S. (Fatty acids, tall-oil, reaction products with diethylenetriamine, Diethylenetriamine)
RID	AMINES, LIQUID, CORROSIVE, N.O.S. (Fatty acids, tall-oil, reaction products with diethylenetriamine, Diethylenetriamine)
ADN	AMINES, LIQUID, CORROSIVE, N.O.S. (Fatty acids, tall-oil, reaction products with diethylenetriamine, Diethylenetriamine)
IMDG	AMINES, LIQUID, CORROSIVE, N.O.S. (Fatty acids, tall-oil, reaction products with diethylenetriamine, Diethylenetriamine)
IATA	Amines, liquid, corrosive, n.o.s. (Fatty acids, tall-oil, reaction products with diethylenetriamine, Diethylenetriamine)

### 14.3. Transport hazard class(es)

ADR	8
RID	8
ADN	8
IMDG	8
IATA	8

### 14.4. Packing group

ADR	II
RID	II
ADN	II
IMDG	II
IATA	II

### 14.5. Environmental hazards

ADR	Environmentally Hazardous
RID	Environmentally Hazardous
ADN	Environmentally Hazardous
IMDG	Marine pollutant
IATA	not applicable

### 14.6. Special precautions for user

ADR	not applicable Tunnelcode: (E)
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

VOC content < 5 %  
(2010/75/EC)

**15.2. Chemical safety assessment**

A chemical safety assessment has not been carried out.

**SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H302 Harmful if swallowed.  
H312 Harmful in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H330 Fatal if inhaled.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H360F May damage fertility.  
H361f Suspected of damaging fertility.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H411 Toxic to aquatic life with long lasting effects.

**Further information:**

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your\_company.com).

**Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.**