Printing date 17.03.2023 Version number: 1 Revision: 17.03.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: FLAW AND CRACK 3 DEVELOPER AERO
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture NA
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Spanjaard (Pty) Ltd

748-750 Fifth Street, Wynberg

Sandton, South Africa, 2090

Tel: +27 11 386 7100

Further information obtainable from:

Clinton Palmer - Operations Executive

clinton@spanjaard.biz

· 1.4 Emergency telephone number: NCEC: +44 1865 407333

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- · Hazard pictograms GHS02, GHS07
- · Signal word Danger
- · Hazard-determining components of labelling:

propan-2-ol

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 2)

Printing date 17.03.2023 Version number: 1 Revision: 17.03.2023

Trade name: FLAW AND CRACK 3 DEVELOPER AERO

(Contd. of page 1)

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 67-63-0	propan-2-ol	25-35%
EINECS: 200-661-7 Index number: 603-117-00-0 RTECS: NT 8050000	Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 RTECS: EJ 4200000	butane, pure Flam. Gas 1A, H220 Acute Tox. 3, H331 Press. Gas (Comp.), H280	25-35%
CAS: 64742-89-8 EINECS: 265-192-2 Index number: 649-267-00-0	Solvent naphtha (petroleum), light aliph. Flam. Liq. 2, H225	25-35%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 RTECS: TX 2275000	propane Flam. Gas 1A, H220 Press. Gas (Comp.), H280	5-10%

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

• 5.2 Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)

Printing date 17.03.2023 Version number: 1 Revision: 17.03.2023

Trade name: FLAW AND CRACK 3 DEVELOPER AERO

(Contd. of page 2)

· 5.3 Advice for firefighters

· Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limi	· Ingredients with limit values that require monitoring at the workplace:	
67-63-0 propan-2-ol		
WEL (Great Britain)	Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm	
AGW (Germany)	Long-term value: 500 mg/m³, 200 ppm 2(II);DFG, Y	
106-97-8 butane, pui	re	
WEL (Great Britain)	Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)	
AGW (Germany)	Long-term value: 2400 mg/m^3 , 1000 ppm 4(II);DFG	

(Contd. on page 4)

Printing date 17.03.2023 Version number: 1 Revision: 17.03.2023

Trade name: FLAW AND CRACK 3 DEVELOPER AERO

	(Contd. of page
64742-89-8 Solve	nt naphtha (petroleum), light aliph.
MAK (Germany)	vgl.Abschn.Xb
74-98-6 propane	
AGW (Germany)	Long-term value: 1800 mg/m^3 , 1000 ppm 4(II);DFG
Ingredients with	piological limit values:
67-63-0 propan-2	-ol
BGW (Germany)	25 mg/l
	Untersuchungsmaterial: Vollblut
	Probennahmezeitpunkt: Expositionsende bzw. Schichtende
	Parameter: Aceton
	25 mg/l
	Untersuchungsmaterial: Urin
	Probennahmezeitpunkt: Expositionsende bzw. Schichtende
	Parameter: Aceton

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Suitable respiratory protective device recommended.

· Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)


(Contd. of page 4)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.03.2023 Version number: 1 Revision: 17.03.2023

Trade name: FLAW AND CRACK 3 DEVELOPER AERO

· Eye/face protection



SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Paste · Colour: White · Odour: Solvent-like · Odour threshold: Not determined. · Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling range > 80 °C (64742-89-8 Solvent naphtha (petroleum), light

aliph.)

· Flammability Not applicable.

· Lower and upper explosion limit

1.5 Vol % (106-97-8 butane, pure) · Lower: 12 Vol % (67-63-0 propan-2-ol) · Upper: -60 °C (106-97-8 butane, pure) · Flash point: 470 °C (74-98-6 propane) · Ignition temperature:

· Decomposition temperature: Not determined. Not determined.

 $\cdot pH$

· Viscosity:

· Kinematic viscosity Not determined. · Dynamic: Not determined.

·Solubility

Fully miscible. · water: · Partition coefficient n-octanol/water (log value) Not determined.

· Vapour pressure at 20 °C: 8,300 hPa (74-98-6 propane)

Density and/or relative density

· Density at 20 °C: 0.44 g/cm^3 · Relative density Not determined. · Vapour density Not determined.

· 9.2 Other information

· Appearance:

· Form: Compressed liquefied gas

· Important information on protection of health and

environment, and on safety.

Product is not selfigniting. · Auto-ignition temperature:

· Explosive properties: Not determined.

· Solvent content:

100.0 % · Organic solvents: · VOC (EC) 100.00 % · Solids content: 0.0 %

· Change in condition

Not applicable. · Evaporation rate

· Information with regard to physical hazard classes

· Explosives Void

(Contd. on page 6)

Printing date 17.03.2023 Version number: 1 Revision: 17.03.2023

Trade name: FLAW AND CRACK 3 DEVELOPER AERO

	(Contd. of page 5)
· Flammable gases	Void
· Aerosols	Extremely flammable aerosol. Pressurised container:
	May burst if heated.
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable	le gases
in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	· LD/LC50 values relevant for classification:	
67-63-0 pr	67-63-0 propan-2-ol	
Oral		5,045 mg/kg (rat)
Dermal	LD50	12,800 mg/kg (rabbit)
Inhalative	LC50/4 h	30 mg/l (rat)
	106-97-8 butane, pure	
Inhalative	LC50/4 h	mg/l (mouse)
		658 mg/l (rat) mg/l (rabbit)
		mg/l (rabbit)

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause drowsiness or dizziness.

(Contd. on page 7)

Printing date 17.03.2023 Version number: 1 Revision: 17.03.2023

Trade name: FLAW AND CRACK 3 DEVELOPER AERO

(Contd. of page 6)

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 1	4: Transport	information
------------------	--------------	-------------

· 14.1 UN number or ID number · ADR, IMDG, IATA	UN1950	
· 14.2 UN proper shipping name · ADR · IMDG · IATA	1950 AEROSOLS AEROSOLS AEROSOLS, flammable	

(Contd. on page 8)

Printing date 17.03.2023 Revision: 17.03.2023 Version number: 1

Trade name: FLAW AND CRACK 3 DEVELOPER AERO

(Contd. of page 7) · 14.3 Transport hazard class(es) $\cdot ADR$ · Class 2 5F Gases. ·Label 2.1 · IMDG · Class 2.1 Gases. · Label 2.1 · IATA · Class 2.1 Gases. · Label 2.1 · 14.4 Packing group · ADR, IMDG, IATA Void · 14.5 Environmental hazards: Not applicable. · 14.6 Special precautions for user Warning: Gases. · Hazard identification number (Kemler code): F-D,S-U· EMS Number: · Stowage Code SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. · Segregation Code SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. · 14.7 Maritime transport in bulk according to IMO *Not applicable.* instruments · Transport/Additional information: · Limited quantities (LQ) 1L

Printing date 17.03.2023 Version number: 1 Revision: 17.03.2023

Trade name: FLAW AND CRACK 3 DEVELOPER AERO

	(Contd. of page
· Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	IL
· Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- · Hazard pictograms GHS02, GHS07
- · Signal word Danger
- Hazard-determining components of labelling:

propan-2-ol

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

(Contd. on page 10)

Printing date 17.03.2023 Version number: 1 Revision: 17.03.2023

Trade name: FLAW AND CRACK 3 DEVELOPER AERO

· REGULATION (EU) 2019/1148

(Contd. of page 9)

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H336 May cause drowsiness or dizziness.

Date of previous version: 13.03.2023

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

 ${\it GHS: Globally Harmonised System of Classification and Labelling of Chemicals}$

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

 $LC 50: Lethal\ concentration,\ 50\ percent$

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids - Category 2

Acute Tox. 3: Acute toxicity - Category 3

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

* Data compared to the previous version altered.